

SMF IC600-S

SYSTEM PART: #82-1600-S
REPLACEMENT CARTRIDGE KIT: #108-015S
RATED CAPACITY (GALLONS): CHLORINE : 50,000 @ 3 PPM*
 CHLORINE : 70,000 @ 2 PPM*
 CHLORAMINE : 15,000 @ 3 PPM*
SCALE INHIBITION (GALLONS) : 75,000
FLOW RATE: 5 GPM
MIN./MAX. PRESSURE: 40– 125 PSI
MIN./MAX. TEMP.: 40°– 100° F
INLET/OUTLET SIZE: 1/2" BARB STANDARD
 17 MODULAR FITTINGS AVAILABLE
SHIPPING WEIGHT: 35 LBS.
DIMENSIONS (W/D/H): 22/9/19"

COFFEE & ESPRESSO APPLICATIONS

FOR: SCALE INHIBITION, CHLORINE,
 CHLORAMINE, SEDIMENT, THMS,
 ORGANICS, TANNINS, BAD TASTE AND
 ODOR REDUCTION

VOLUME: HIGH

SPECIFIED TO:

- INHIBIT SCALE BUILD-UP
- REDUCE PITTING OF HEATING ELEMENTS IN BREWING EQUIPMENT
- IMPROVE TASTE OF BREWED BEVERAGES
- PROVIDE SAFE, CLEAN INGREDIENT WATER
- REDUCE CHLORINE, CHLORAMINE, BAD TASTES AND ODORS, TOTAL ORGANIC COMPOUNDS, TANNINS AND TRIHALOMETHANES

FILTER BENEFITS:

- ONE FILTER CAN DO IT ALL: DIRT REDUCTION, CHEMICAL REDUCTION, CHLORAMINES REDUCTION AND SCALE INHIBITION! NO PRE-FILTER REQUIRED!
- THE FIRST JUMBO SANITARY FILTER ON THE MARKET!
- NYLON CONSTRUCTION TO WITHSTAND HIGH PRESSURE!
- FILTER PERFORMANCE GUARANTEE!
- 40 TIMES MORE DIRT HOLDING CAPACITY THAN CONVENTIONAL CARBON BLOCK FILTERS AND OTHER POLYPROPYLENE SEDIMENT FILTERS!
- 30 TIMES THE CHLORAMINE REDUCTION OF A CONVENTIONAL CARBON BLOCK!
- LOW PRESSURE DROP!
- MODULAR FILTER DESIGN FOR UP TO 50% LESS INSTALLATION TIME!
- QUICKLY ADD FITTINGS FOR EXTRA FILTER CAPACITY WITH NO TOOLS REQUIRED!

TECHNOLOGY:

- ULTRA HIGH POROSITY CARBON WITH MICRO STRUCTURE
- SILIPHOS

APPLICATIONS:

- COFFEE BREWERS
- ESPRESSO & CAPPUCCINO MACHINES



*Independently tested by an E.P.A. approved laboratory to ANSI/NSF Standard 42 specifications for the reduction of Particulate Class I, Chlorine, Chloramine, Taste and Odor.



Base system has been tested and certified by NSF International against ANSI/NSF Std. 42. Please visit www.nsf.org for specifications.

Do not use with water that is microbiologically unsafe or of unknown quality.

selecto

3980 LAKEFIELD COURT, SUWANEE, GA 30024 USA
 800-635-4017 • 678-475-0799 • WWW.SELECTOINC.COM

© 2008 Selecto Scientific, Inc. • All Rights Reserved.

805-012 Rev. 03-27-08