

SMF IC620-S

SYSTEM PART: #80-6200-S
REPLACEMENT CARTRIDGE: #108-025S
RATED CAPACITY (GALLONS): CHLORINE : 100,000
CHLORAMINE *: 30,000
SCALE INHIBITION : 75,000
FLOW RATE: 5 GPM
MIN./MAX. PRESSURE: 40– 125 PSI
MIN./MAX. TEMP.: 40°– 100° F
INLET/OUTLET SIZE: 3/8" BARB STANDARD
17 MODULAR FITTINGS AVAILABLE
SHIPPING WEIGHT: 37 LBS.
DIMENSIONS (W/D/H): 22/9/ 29"



* Independently tested by an E.P.A. approved laboratory to ANSI/NSF Standard 42 & 53 specifications for the reduction of Cyst, Particulate Class I, Chlorine, Chloramine, Taste and Odor.

FOUNTAIN & ICE APPLICATION

FOR: CHLORINE, CHLORAMINE, SEDIMENT,
THMS, ORGANICS, TANNINS, BAD TASTE
AND ODOR REDUCTION, & SCALE
INHIBITION
VOLUME: HIGH

SPECIFIED TO:

- IMPROVE TASTE OF FOUNTAIN BEVERAGES
- PROVIDE SAFE, CLEAN INGREDIENT WATER FOR BEVERAGES & ICE
- REDUCE CHLORINE, CHLORAMINE, BAD TASTES AND ODORS, TOTAL ORGANIC COMPOUNDS, TANNINS AND TRIHALOMETHANES
- INHIBIT HARDNESS MINERALS & SCALE BUILD-UP
- INCREASE FOUNTAIN SALES
- INCREASE CARBONATION

FILTER BENEFITS:

- ONE FILTER CAN DO IT ALL: DIRT REDUCTION, CHEMICAL REDUCTION AND CHLORAMINES REDUCTION! NO PRE-FILTER REQUIRED!
- THE FIRST JUMBO SANITARY FILTER ON THE MARKET!
- NYLON CONSTRUCTION TO WITHSTAND HIGH PRESSURE!
- FILTER PERFORMANCE GUARANTEE!
- 40 TIMES MORE DIRT HOLDING CAPACITY THAN CONVENTIONAL CARBON BLOCK FILTERS AND OTHER POLYPROPYLENE SEDIMENT FILTERS!
- 30 TIMES THE CHLORAMINE REDUCTION OF A CONVENTIONAL CARBON BLOCK!
- LOW PRESSURE DROP!
- MODULAR FILTER DESIGN FOR UP TO 50% LESS INSTALLATION TIME!
- QUICKLY ADD FITTINGS FOR EXTRA FILTER CAPACITY WITH NO TOOLS REQUIRED!

TECHNOLOGY:

- ULTRA HIGH POROSITY CARBON WITH MICRO-STRUCTURE

APPLICATIONS:

- 1 TO 2 CARBONATORS
- FOUNTAIN AND MULTIUSE APPLICATION SUCH AS COFFEE, TEA AND ICE



Base system has been tested and certified by NSF International against ANSI/NSF Std. 53 and ANSI/NSF Std. 42. Please visit www.nsf.org for specifications.
Do not use with water that is microbiologically unsafe or of unknown quality.

selecto

3980 LAKEFIELD COURT, SUWANEE, GA 30024 USA
800-635-4017 • 678-475-0799 • WWW.SELECTOINC.COM

© 2007 Selecto Scientific, Inc. • All Rights Reserved.

805-028 Rev. 10-18-07